

# day Graphica 3610...

## Make high performance less challenging...

The dayGraphica 3610 is one of the most durable, flexible and versatile blankets from DAY International. dayGraphica 3610 handles a broad range of printing job requirements and keeps on going... whatever the age of your press.

DAY International's technology group combined the best components from the dayGraphica product line to produce a unique construction that reduces gauge loss, increases durability and will stand up to challenging pressroom conditions. The 3610 can handle the entire range of printing applications from high quality commercial web to sheet fed jobs. It's ground surface allows for uniform gauge which translates to longer blanket life, better print quality, reduced press down time and running costs, increasing pressroom efficiency.

#### Benefits **Features** Redesigned enhanced Compensates for press wear and imperfections. Provides compressible layer optimal nip pressure that provides excellent print contrast and solid ink densities. Ground and buffed surface Uniform gauge thickness and consistency. Ideal surface texture for optimum ink transfer. Excellent release characteristics for precise web control. High density carcass Greater gauge stability, providing longer life. Excellent smash resistance, rebounds quickly. Compatible rubber surface Provides quick release, ease of wash-up and reduces swelling. Compatible with newer pressroom chemistries.

## Optimise Your On-Press Performance

Over the years, Day's printing technologists and pressroom chemists have learned the dynamics between pressroom chemicals and printing blankets play a vital role in on-press performance and profitability. And they've learned how to analyse these dynamics to help printers resolve problems and optimise their printing results.

Day's laboratory experts, technical support team and sales consultants work together with printers to recommend the right combination of pressroom chemicals and printing blankets to achieve optimum performance. A consultative service offered only by Day International.

## Product Specifications...

Colour:	Green
Surface:	Ground
Thickness:	1.95mm
	1.70mm
Overall Hardness:	78° Shore A
Compressibility:	0.14mm at 1060 kpa
	0.19mm at 2060 kpa
Elongation:	<0.70% at 10 N/mm
Tensile Strength:	>60 N/mm
Face Compound:	Solvent resistant rubber blend



For more information about dayGraphica and other Day International products, e-mail us at salesuk@day-intl.com or visit us at www.dayintl.com